Alloy Master Link Grade 100 (Peerless)

CATALOG (SKU) NUMBER: PEER-8451

- For use with grade 80 or 100 chain slings, wire rope, and synthetic assemblies.
- Design factor is 4:1.
- Meet or exceed all requirements of ASME B30.26.
- Proof tested in accordance with ASTM A952.
- Available in Chinese import or U.S.A. domestic upon request.



G-100 Masterlink



oblong master link

PACIFIC Industrial Supply

Product Specifications

ALLOY MASTER LINKS (PEERLESS) GRADE 100								
PART NUMBER	SIZE (IN)	SIZE (MM)	WORKING LOAD LIMIT (LBS)	DIMENSIONS (IN)			WEIGHT EA (LBS)	COUNTY OF ORIGIN
				A	B	C		
PEER-8851000	1/2	13	7,000	0.512	2.362	4.331	0.7	GERMANY
PEER-8851100	5/8	16	11,400	0.63	2.362	4.331	1.2	GERMANY
PEER-8851200	3/4	18	12,300	0.709	2.953	5.315	1.8	GERMANY
PEER-8851300	7/8	23	17,200	0.866	3.543	6.299	3.3	GERMANY
PEER-8851400	1	27	29,900	1.024	3.937	7.087	5.1	GERMANY
PEER-8851500	1-1/4	33	35,200	1.26	4.331	7.874	8.6	GERMANY
PEER-8851600	1-1/2	38	68,000	1.496	5.906	10.827	16.5	GERMANY
PEER-8851700	1-3/4	45	84,900	1.772	7.087	13.386	28.2	GERMANY
PEER-8851800	2	50	102,600	1.969	7.48	13.78	36.4	GERMANY
PEER-8851900	2-1/4	60	143,100	2.362	7.874	15.748	59.5	GERMANY