

Alloy Swivel Hoist Hook With Latch

CATALOG (SKU) NUMBER: CA-SH/CT-395

- Heat Treated Alloy Steel.
- Design Factor is 5:1.
- All Hooks Drilled For Latch.
- Swivel hooks are not designed to swivel under load.



Swivel Hook Alloy



swivel hoist hookDM

Product Specifications

ALLOY SWIVEL HOIST HOOK (WITH LATCH)															REPLACEMENT LATCH PART NUMBER (IMPORT)	REPLACEMENT LATCH PART NUMBER (DOMESTIC)	
	SIZE/WORKING LOAD LIMIT (TONS)	IMPORT PART NUMBER	DOMESTIC PART NUMBER	WEIGHT (LBS)	DIMENSIONS (IN)												
				A	B	C	D	E	F	G	H	I	J	K			L
1	CA-SH13952215	CT-2215	.90	2.0000	0.0000	0.2500	0.9375	0.0313	0.8750	0.7813	0.9063	0.5625	0.6250	0.6250	0.3750	I50330	CT-T7502101
1.5	-	CT-3952315	1.1	2.5000	0.2500	0.5000	0.2500	0.0313	0.8750	0.8438	0.9688	0.6250	0.6875	0.4375	0.5000	-	CT-T7502101
2	CA-SH23952415	CT-2415	1.6	2.5000	0.2500	0.5000	0.5625	0.1250	0.0313	0.0313	0.1250	0.6875	0.3125	0.8125	0.5000	I50340	CT-7506495
3	CA-SH33952515	CT-2515	2.7	3.0000	0.6250	0.7500	0.0000	0.2500	0.1250	0.1563	0.3125	0.8125	0.1875	0.4375	0.6250	I50345	CT-7506495
4.5	CA-SH53952715	CT-2715	4.5	3.5000	0.7500	0.0000	0.9375	0.5313	0.9375	0.4375	0.6250	0.0625	0.4375	0.0000	0.7500	I50350	CT-7506695
7	CA-SH73952915	CT-2915	10	4.5000	0.2500	0.5000	0.4688	0.9688	0.6563	0.8125	0.1250	0.3750	0.3750	0.6250	0.0000	I50352	CT-7506895
11	-	CT-3953115	18.25	5.6250	0.8438	0.1250	0.3438	0.1250	0.0000	0.2500	0.2500	0.6250	0.5000	0.0000	0.5625	-	CT-7507095
15	-	CT-3953215	20	5.6250	0.7500	0.1250	0.8125	0.5625	0.1250	0.5625	0.9375	0.8125	0.0313	0.2500	0.2500	-	CT-7507295