

Carbon Steel Single Flemish Swage Sleeve (Domestic)

CATALOG (SKU) NUMBER: SLEEVE FLEMISH

- ESCO carbon steel single sleeves for Flemish eyes meet industry standards for efficiency and strength.
- Manufactured from specially selected steels, these sleeves are produced under rigid quality assurance guidelines.
- Careful forming, followed by custom heat treating, ensure accurate rope fit, component consistency and maximum material performance during swaging and on the job.
- ESCO carbon steel single swage sleeves are available in sizes to fit wire rope from 1/4in to 2-1/2in.



150529_0423PacificIndustrial



Flemish Sleeve Carbon
DimMap





150529_0424PacificIndustrial

Product Specifications

CARBON STEEL FLEMISH SWAGE SLEEVE (DOMESTIC)												
DIMENSIONS (IN)												
PART NUMBER	WIRE ROPE DIAMETER (IN)	WEIGHT EACH (LBS)	BEFORE SWAGE	AFTER SWAGE DIAMETER	BOX QUANTITY	USE ESCO SWAGE DIE SIZE	A	B	C	D	E	TAPER
			4058006	1/4								
4058007	5/16	0.17	1.5000	.4375	.4375	.6250	.9375	.7700	1.00			3/8IN TAPER
4058008	3/8	0.14	1.5000	.4375	.5000	.6875	.9375	.7700	1.00			3/8IN TAPER
4058009	7/16	0.32	2.0000	.6250	.5625	.8750	1.2500	1.0200	1.00			1/2IN TAPER
4058010	1/2	0.24	2.0000	.6250	.6250	.8750	1.2500	1.0200	1.00			1/2IN TAPER
4058011	9/16	0.42	2.7500	.6875	.6875	1.0000	1.5000	1.2300	1.50			5/8IN TAPER
4058012	5/8	0.50	2.7500	.6875	.7500	1.1250	1.5000	1.2300	1.50			5/8IN TAPER
4017630	3/4	0.90	3.1875	.8125	.9375	1.3125	1.7500	1.4500	1.50			3/4IN TAPER
4015387	7/8	1.40	3.5625	.9375	1.0625	1.5000	2.0000	1.7000	2.25			7/8IN TAPER
4015388	1	2.00	4.0000	1.2500	1.1250	1.7500	2.3125	2.8900	2.00			1IN OPEN CHANNEL THEN 1IN TAPER
4015389	1-1/8	2.60	4.6250	1.3125	1.2500	1.9375	2.5000	3.1000	2.00			1-1/8IN OPEN CHANNEL THEN 1-1/8IN TAPER

CARBON STEEL FLEMISH SWAGE SLEEVE (DOMESTIC)										
4015390	1-1/4	3.40	5.2500	1.3750	1.4375	1.1875	2.812	2.3000	10	1-1/4IN OPEN CHANNEL THEN 1-1/4IN TAPER
4015391	1-3/8	4.00	5.8750	1.5625	1.5000	2.3750	3.000	2.5200	-	1-1/2IN OPEN CHANNEL THEN 1-3/8IN TAPER
4015392	1-1/2	5.20	6.3125	1.7500	1.6875	2.6250	3.250	2.6700	-	1-1/2IN FIRST STAGE THEN 1-1/2IN TAPER