PACIFIC
Industrial Supply

# Compact Swaged 6X25 EIPS Grade IWRC Logging Wire Rope

## CATALOG (SKU) NUMBER: 6X25

- Compact swaged 6X25 wire rope is typically used for logging rope. It offers excellent crushing resistance and excellent abrasion resistance.
- Rotary swaged and hammered agian to produce a compact cross section with minimal valleys between strands than a standard 6x19 class or even a 6X26 swaged wire rope. This design helps reduce wear to sheaves and prevents crushing of the wire rope when spooling. Highest strength rope available in a 6X19 classification.
- Manufactured in accordance with RR-W-410 standards, preformed, right regular lay. Galvanized wire rope is drawn galvanized.
- Available in import or domestic.
- Mill test certifications available upon request.
- Nominal breaking strengths slightly vary by manufacturer.

PACIFIC Industrial Supply

# Product Specifications

| LOGGING WIRE ROPE 6X25 COMPACT SWAGED EIPS GRADE IWRC | | |
|---|---|---|
| SIZE (IN) | APROXIMATE WEIGHT PER FOOT (LBS) | NOMINAL BREAKING STRENGTH (LBS) |
| 1/2 | 0.630 | 37,120 |
| 9/16 | 0.790 | 46,900 |
| 5/8 | 0.970 | 57,480 |
| 3/4 | 1.390 | 79,800 |
| 7/8 | 1.870 | 103,780 |
| 1 | 2.360 | 135,700 |
| 1-1/8 | 2.890 | 169,620 |
| 1-1/4 | 3.430 | 203,560 |
| 1-3/8 | 4.210 | 238,940 |