

Polyester Roundslings

CATALOG (SKU) NUMBER: OS-OL

- Polyester roundslings offer excellent resistance against UV rays, rot, and mildew.
- They are lightweight, easy to handle and store, and only have a 3% elongation
- Solid tube construction non-sewn edge on cover.
- Consists of an endless loop of 100% polyester fiber.
- Very pliable compared to wire rope or chain rigging, even contours itself around the load being picked.
- All slings conform to standards/ specifications ASME B30.9 and WSTDA.
- Made in the U.S.A.
- Available as return eye style upon request.
- Other color/ weight options available upon request.
- Custom lengths up to 60ft available upon request.



Polyester Round Slings A



Polyester Round Slings B





Polyester Round Slings C

Product Specifications

| POLYESTER ROUNDSLINGS (DOMESTIC) | | | | | | |
|----------------------------------|--------------------------|--------|-------------|--------------------------|--------|--------|
| PART NUMBER | APRIXIMATE DIAMETER (IN) | COLOR | LENGTH (FT) | WORKING LOAD LIMIT (LBS) | | |
| | | | | VERTICAL | CHOKER | BASKET |
| OS-OL1-3 | 0.60 | PURPLE | 3 | 2,650 | 2,120 | 5,300 |
| OS-OL1-3 | 0.60 | PURPLE | 4 | 2,650 | 2,120 | 5,300 |
| OS-OL1-6 | 0.60 | PURPLE | 6 | 2,650 | 2,120 | 5,300 |
| OS-OL1-8 | 0.60 | PURPLE | 8 | 2,650 | 2,120 | 5,300 |
| OS-OL1-10 | 0.60 | PURPLE | 10 | 2,650 | 2,120 | 5,300 |
| OS-OL1-12 | 0.60 | PURPLE | 12 | 2,650 | 2,120 | 5,300 |
| OS-OL1-14 | 0.60 | PURPLE | 14 | 2,650 | 2,120 | 5,300 |
| OS-OL1-16 | 0.60 | PURPLE | 16 | 2,650 | 2,120 | 5,300 |
| OS-OL1-18 | 0.60 | PURPLE | 18 | 2,650 | 2,120 | 5,300 |
| OS-OL1-20 | 0.60 | PURPLE | 20 | 2,650 | 2,120 | 5,300 |
| OS-OL2-4 | 0.80 | GREEN | 4 | 5,300 | 4,240 | 10,600 |
| OS-OL2-6 | 0.80 | GREEN | 6 | 5,300 | 4,240 | 10,600 |
| OS-OL2-8 | 0.80 | GREEN | 8 | 5,300 | 4,240 | 10,600 |
| OS-OL2-10 | 0.80 | GREEN | 10 | 5,300 | 4,240 | 10,600 |
| OS-OL2-12 | 0.80 | GREEN | 12 | 5,300 | 4,240 | 10,600 |
| OS-OL2-14 | 0.80 | GREEN | 14 | 5,300 | 4,240 | 10,600 |
| OS-OL2-16 | 0.80 | GREEN | 16 | 5,300 | 4,240 | 10,600 |
| OS-OL2-18 | 0.80 | GREEN | 18 | 5,300 | 4,240 | 10,600 |

| POLYESTER ROUNDSLINGS (DOMESTIC) | | | | | | |
|----------------------------------|------|--------|----|--------|--------|--------|
| OS-OL2-20 | 0.80 | GREEN | 20 | 5,300 | 4,240 | 10,600 |
| OS-OL3-4 | 1.00 | YELLOW | 4 | 8,400 | 6,720 | 16,800 |
| OS-OL3-6 | 1.00 | YELLOW | 6 | 8,400 | 6,720 | 16,800 |
| OS-OL3-8 | 1.00 | YELLOW | 8 | 8,400 | 6,720 | 16,800 |
| OS-OL3-10 | 1.00 | YELLOW | 10 | 8,400 | 6,720 | 16,800 |
| OS-OL3-12 | 1.00 | YELLOW | 12 | 8,400 | 6,720 | 16,800 |
| OS-OL3-14 | 1.00 | YELLOW | 14 | 8,400 | 6,720 | 16,800 |
| OS-OL3-16 | 1.00 | YELLOW | 16 | 8,400 | 6,720 | 16,800 |
| OS-OL3-18 | 1.00 | YELLOW | 18 | 8,400 | 6,720 | 16,800 |
| OS-OL3-20 | 1.00 | YELLOW | 20 | 8,400 | 6,720 | 16,800 |
| OS-OL5-4 | 1.20 | RED | 4 | 13,200 | 10,560 | 26,400 |
| OS-OL5-6 | 1.20 | RED | 6 | 13,200 | 10,560 | 26,400 |
| OS-OL5-8 | 1.20 | RED | 8 | 13,200 | 10,560 | 26,400 |
| OS-OL5-10 | 1.20 | RED | 10 | 13,200 | 10,560 | 26,400 |
| OS-OL5-12 | 1.20 | RED | 12 | 13,200 | 10,560 | 26,400 |
| OS-OL5-14 | 1.20 | RED | 14 | 13,200 | 10,560 | 26,400 |
| OS-OL5-16 | 1.20 | RED | 16 | 13,200 | 10,560 | 26,400 |
| OS-OL5-18 | 1.20 | RED | 18 | 13,200 | 10,560 | 26,400 |
| OS-OL5-20 | 1.20 | RED | 20 | 13,200 | 10,560 | 26,400 |
| OS-OL7-4 | 1.75 | BLUE | 4 | 21,200 | 17,000 | 42,400 |
| OS-OL7-6 | 1.75 | BLUE | 6 | 21,200 | 17,000 | 42,400 |
| OS-OL7-8 | 1.75 | BLUE | 8 | 21,200 | 17,000 | 42,400 |

| POLYESTER ROUNDSLINGS (DOMESTIC) | | | | | | |
|----------------------------------|------|------|----|--------|--------|--------|
| OS-OL7-10 | 1.75 | BLUE | 10 | 21,200 | 17,000 | 42,400 |
| OS-OL7-12 | 1.75 | BLUE | 12 | 21,200 | 17,000 | 42,400 |
| OS-OL7-14 | 1.75 | BLUE | 14 | 21,200 | 17,000 | 42,400 |
| OS-OL7-16 | 1.75 | BLUE | 16 | 21,200 | 17,000 | 42,400 |
| OS-OL7-18 | 1.75 | BLUE | 18 | 21,200 | 17,000 | 42,400 |
| OS-OL7-20 | 1.75 | BLUE | 20 | 21,200 | 17,000 | 42,400 |
| OS-OL8-4 | 2.25 | GRAY | 4 | 31,700 | 25,300 | 63,400 |
| OS-OL8-6 | 2.25 | GRAY | 6 | 31,700 | 25,300 | 63,400 |
| OS-OL8-8 | 2.25 | GRAY | 8 | 31,700 | 25,300 | 63,400 |
| OS-OL8-10 | 2.25 | GRAY | 10 | 31,700 | 25,300 | 63,400 |
| OS-OL8-12 | 2.25 | GRAY | 12 | 31,700 | 25,300 | 63,400 |
| OS-OL8-14 | 2.25 | GRAY | 14 | 31,700 | 25,300 | 63,400 |
| OS-OL8-16 | 2.25 | GRAY | 16 | 31,700 | 25,300 | 63,400 |
| OS-OL8-18 | 2.25 | GRAY | 18 | 31,700 | 25,300 | 63,400 |
| OS-OL8-20 | 2.25 | GRAY | 20 | 31,700 | 25,300 | 63,400 |