

Stainless Steel 2-Piece Duplex Swaging Sleeve (Domestic)

CATALOG (SKU) NUMBER: SLEEVE DUPLEX 2PC

- ESCO stainless steel duplex sleeves provide the quickest and simplest way to make strong swaged turnback eyes in wire rope.
- Duplex sleeves permit easy adjustment of eye size.
- Grommets, plain eyes and tight thumbed eyes can be made quickly and precisely every time without splicing or die changes.
- These swage sleeves are cast with the popular ESCO 40SS stainless steel, created specifically for swaging.
- High initial ductility allows ESCO stainless steel to flow evenly around the wire rope during swaging, for total gripping strength and extremely high crack and fracture resistance.
- During swaging, ESCO stainless steel hardens more than any other swaging steel to provide toughness, on-the-job durability and corrosion resistance.



SS Swage Duplex 2pc2



150529_0437PacificIndustrial



150529_0438PacificIndustrial



SS Duplex Swage 2pc

Product Specifications

STAINLESS STEEL 2-PIECE DUPLEX SWAGE SLEEVE (DOMESTIC)									
PART NUMBER	WIRE ROPE DIAMETER (IN)	WEIGHT EACH (LBS)	DIMENSION (IN)						
			BEFORE SWAGE			AFTER SWAGE		BOX QUANTITY	USE ESCO SWAGE DIE SIZE
			A (LENGTH)	B (WIDTH)	C (HEIGHT)	A (LENGTH)	DIAMETER		
5108922	1/2	0.20	1.0625	.9375	1.3750	1.1250	1.0100	100	1/2IN OPEN CHANNEL
5108923	9/16	0.30	1.2500	1.1875	1.6875	1.4375	1.2700	100	5/8IN OPEN CHANNEL
5103275	5/8	0.30	1.0625	1.3125	1.8125	1.1875	1.2700	100	5/8IN OPEN CHANNEL
5108652	3/4	0.50	1.1875	1.3750	2.1250	1.4375	1.5300	100	3/4IN OPEN CHANNEL
5103274	7/8	0.70	1.3750	1.7500	2.5000	1.6250	1.7600	50	7/8IN OPEN CHANNEL

STAINLESS STEEL 2-PIECE DUPLEX SWAGE SLEEVE (DOMESTIC)									
5103264	1	1.00	1.5625	1.8125	2.7500	1.8125	2.0400	50	1IN OPEN CHANNEL
5103265	1-1/8	1.50	1.8750	2.0000	3.1875	2.1250	2.2600	30	1-1/8IN OPEN CHANNEL
5104997	1-1/4	2.00	2.1250	2.3750	3.3750	2.5000	2.5100	20	1-1/4IN OPEN CHANNEL
5105001	1-3/8	2.00	2.1250	2.3125	3.5625	2.5000	2.5100	20	1-1/4IN OPEN CHANNEL
5104996	1-1/2	2.00	2.2500	2.5000	3.8750	2.6250	2.7000	20	1-1/2IN OPEN CHANNEL